Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase. Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best guality finish for your specific project.

# **DANGER** KEEP OUT OF REACH OF CHILDREN

Resene

# Moss & Mould Killer

exterior/interior

#### SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Cause severe skin burns and eye damage. May be corrosive to metals. Toxic to aquatic life with long lasting effects

1183401B 5/20

#### PRECAUTIONS

DO NOT BREATHE MIST, VAPOURS OR SPRAY. Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Keep only in original packaging. Store locked up. Wear protective gloves and clothing, eye and face protection. Avoid release to the environment. Absorb spillage to prevent material damage. Collect spillage.

#### FIRST AID

IF SWALLOWED: Rinse mouth, Do NOT induce vomiting, Call a POISON CENTRE, doctor or first aider if you feel unwell

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTRE, doctor or first aider if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing and wash before reuse. Rinse skin with plenty of soap and water, if skin irritation or rash occurs get medica advice or attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. Immediately call a POISON CENTRE doctor or first aider.

Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)

or call Resene 0800 737 363. If medical advice is needed: have product container at hand.

CONTAINS: Sodium Hypochlorite 50-170 ams/L

For use as a cleaner and moss and mould killer.

For full technical instructions see Data Sheet D80

Resene Moss & Mould Killer is a hypochlorite based wash designed to kill and bleach most common moulds and fungus.

### Preparation

 Mould is a major cause of paint disfigurement. It destroys the paint's fresh clean appearance and if left unchecked shortens the life of the paint film. Unless removed within a few months of its appearance, mould penetrates the body of the existing film and once firmly established, will grow through subsequent paint coatings impairing adhesion and ruining the appearance of paintwork

 On painted surfaces mould looks like dirt and frequently the two cannot. be visually distinguished. The most common species are black but others can be brown or green. Resene Moss & Mould Killer will bleach and kill most common moulds and fungi. This generally distinguishes between mould and dirt as dirt will usually remain black and not be bleached. • Use on cementitious surfaces, weathered timber, walls and ceilings

and wherever mould is present. Use Resene Moss & Mould Killer prior to

This product may be used to clean a wide variety of surfaces. If the surface you propose to clean is not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

## Application

 Mix one part Resene Moss & Mould Killer to five parts water. Apply by brush or spray at a rate to suit the degree of infestation present. Light infestation - 20 square metres per litre, medium infestation - 10 square metres per litre, heavy infestation - 5 square metres per litre.

 Wear adequate protection especially when spraying. Use overalls, gloves, suitable footwear, eve protection, and a suitable mist mask when airborne mist is present

 Leave overnight after application to achieve full kill.
 Scrub vigorously with water to remove dead mould residues prior to painting. Rinse with clean water.
Heavy infestations may require a second treatment.

Waterblasting is a good subsequent treatment.

#### CAUTION

 Never mix Resene Moss & Mould Killer with acids, ammonium compounds or amines

Do not add Resene Moss & Mould Killer to paint.

 Mild steel, stainless steels, copper, brass, bronze, iron and rubber are attacked by Resene Moss & Mould Killer and are unsuitable materials for

 Reserve us reserve muss a work of the user and a displaced in the rate of the storage or application equipment.
 Reserve Moss & Mould Killer is a strong bleaching agent and even diluted can damage/bleach fabrics, textiles, carpets and foliage. Avoid splashes or overspray. Immediately flush affected areas with large amounts of clean water

 Do not allow the product to come into contact with plants, stormwater outlets, streams or animals. May kill aquatic life if allowed to enter the stormwater system. Divert all roof run-off to a sewer or alternative catchment system.

Please ensure that use of this product is compatible with the substrate and surface preparation method. Resene does not accept any responsibility for the <u>application</u> of incorrect product to substrate. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

In Australia: Resene Paints (Aust) Limited 7 Production Ave, PO Box 924, Beenleigh, Old 4207 Ph 1800 738 383 Visit www.resene.com.au



In New Zealand: Resene Paints I td Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045 Ph 04 577 0500 Visit www.resene.co.nz

YE

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAI, an accredited certification body. Printed on environmentally responsible paper, which meets with the requirements of environmental management system EMAS. Printed using de-inkable toners for recycling with no solvent emissions.

# Quick check

Use on: Cementitious surfaces, weathered timber, walls and ceilings and wherever mould is present. Appearance: Water thin, slightly greenish/vellow liquid.

Mixing ratio: One part Resene Moss & Mould Killer to five parts clean water.

Usage (diluted mix): Light infestation: 20 square metres per litre per coat. Medium infestation: 10 square metres per litre per coat. Heavy infestation: 5 square metres per litre per coat

No. of applications: Usually one. Heavy infestations may require retreatment after scrubbing.

Application method: Brush, knapsack, garden or conventional spray.

Thinning and clean up: Water.

⋹~

CORROSIVE

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

