



Transform a drab shed wall into a fresh feature with a little bit of help from Resene.

★☆☆ Difficulty level ★ easy ★★ moderate ★★★ challenging

Weekend DIY with Mark Rayner – 48

You will need:

- Bucket
- Garden hose with clean running water
- Paintbrush
- Resene Lumbersider tinted to Resene Sweet Corn
- Resene Moss & Mould Killer
- Resene Paint Prep and Housewash
- Resene Quick Dry waterborne primer undercoat
- Rubber gloves
- Sandpaper
- Stiff-bristled brush



Step one
Mix one part Resene Moss & Mould Killer to five parts clean water.



Step two
Wearing rubber gloves, brush the shed wall with the solution until it's thoroughly soaked and leave for 48 hours.



Step three
Mix one part Resene Paint Prep and Housewash to three parts clean water.



Step four
Scrub the shed wall vigorously with the solution using a stiff-bristled brush.



Step five
Rinse the shed wall thoroughly with clean water and allow to dry.



Step six
Sand any areas of flaking paint and then brush off any sanding residue.




Step seven
Spot prime any areas of bare wood with Resene Quick Dry and allow two hours to dry.



Step eight
Apply two coats of Resene Sweet Corn to the shed wall, allowing two hours for each coat to dry.



To get the look:
Mark painted the plant shelf with Resene Lumbersider tinted to Resene Quarter Moonbeam.



Other ideas:
For a fresh green effect paint the shed with Resene Lumbersider tinted to Resene Soft Apple.

For more ideas and inspiration visit your local Resene ColorShop or www.resene.com/colorshops.

Check out more project ideas online www.resene.com/projects.