

net contents 1 litre

LL1579001 4/19

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. May be harmful if swallowed. Causes serious eye irritation. May be harmful in contact with the skin. Causes mild skin irritation. May cause an allergic skin reaction. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.

PRECAUTIONS

DO NOT BREATHE DUST, FUMES, GAS, MISTS, VAPOURS, OR SPRAYS. DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.

Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Store locked up. Wear protective gloves and clothing, eye and face protection. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and intrinsically safe equipment. Use non-sparking tools. Take action to prevent static discharge. Avoid release to the environment. Obtain special instructions before use.

FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation or rash occurs get medical advice or attention. Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention. If exposed or concerned get medical advice or attention.

If medical advice is required have product container or label at hand.

Further information can be obtained from
AUST: POISONS INFORMATION CENTRE 131 126
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)
or call Resene 0800 737 363.

For use as a decorative/protective coating.

SPILLS: wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with Resene Brush Cleaner or mineral turps. Do not allow mineral turps to enter any drains. Refer to your local Council for disposal of dirty mineral turps.

FIRE: Use foam, carbon dioxide or dry chemical powder.

WARNING

KEEP OUT OF REACH OF CHILDREN

Resene

AquaLAQ

NGR Primer Sealer

interior solventborne



Resene AquaLAQ NGR Primer Sealer is a single pack solventborne non grain raising primer sealer designed for kitchens, shop fittings and furniture finishing. Designed for easy overcoating with Resene AquaLAQ Colour Coat. The rheology of Resene AquaLAQ minimises applicator error.

Preparation

• Ensure substrates to be coated are in sound condition, dry, free from dirt, dust, loose material, oil (including mineral oil based wood finishes or similar) and salt.

• **All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**

• For new work ensure the surface is sanded to a smooth finish and dusted off. Round all sharp edges. Ensure the surface is dry before painting.

• This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

Application

• Ensure you have read the detailed Resene AquaLAQ application sheet available from Resene prior to application of product.

• Apply 1-2 coats by spray allowing at least 30 minutes before overcoating.

• Maintain good ventilation throughout the drying and post application curing period to ensure the paint is properly cured. This may require use of an extraction system. Multiple air changes are required during application and until product is cured sufficiently.

Ensure humidity is less than 65% and temperature 15-25°C for ideal application and curing. Poor ventilation may affect appearance and performance.

Maintenance

(after a minimum of four weeks' drying) See the Resene Caring for your paint finish brochure or the Resene website for full cleaning instructions.

Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information.



UN NO. 1263 - PAINT RELATED MATERIAL



In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Ph 1800 738 383 Visit www.resene.com.au
In New Zealand: Resene Paints Limited
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045
Ph (04) 577 0500 Visit www.resene.co.nz
Resene Automotive & Light Industrial
PO Box 62282, Mt Wellington Mail Centre, Auckland 1060
Call (09) 259 2738, Fax (09) 259 2937
visit www.rali.co.nz or email us at info@rali.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAL, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

Quick check

Use on: Kitchens, shop fittings and furniture finishing, over correctly prepared MDF board and wood substrates. May also be used on window joinery.

Coverage: 8-10 square metres per litre per coat.

Dry time (minimum): Touch dry 10-15 minutes. Maintain good ventilation throughout the drying and post application curing period to ensure the paint is properly cured. This may require use of an extraction system. Multiple air changes are required during application and until product is cured sufficiently. Ensure humidity is less than 65% and temperature 15-25°C for ideal application and curing. Poor ventilation may affect appearance and performance.

Recoat time (minimum): 30 minutes.

Usual number of coats: 1-2.

Application method: Spray - pressure pot, suction or gravity. Small areas may be brushed or rolled if necessary.

Thinning: Do not thin. Consult Resene if needed.

Clean up: Mineral turps.

Colour range: Light grey.

Before use: Stir well with a wide flat stirrer, mixing from the bottom of the pail towards the top.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

FLAMMABLE LIQUID AND VAPOUR

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause standard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.