

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase. Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

Quick check

Resene

Aquapel & Terracotta Sealer

waterborne exterior/interior

KEEP OUT OF REACH OF CHILDREN



LL2791050F
8-24

SHAKE WELL
BEFORE USE

Resene Aquapel & Terracotta Sealer is a water repellent treatment formulated to help control efflorescence and give a long-term water beading effect to deter water penetration. Use on its own or as a primer under waterborne coatings. It will not prevent the penetration of driving rain or water under hydrostatic pressure.

Use on: Most porous building materials, terracotta and as a protective finish over Resene FX Faux Rust Effect.

Gloss level: None, fully penetrating.

Coverage: It will vary according to substrate porosity, but typically less than 2 square metres per litre.

Dry time (minimum): Penetrates – up to 48 hours at 20°C.

Recoat time (minimum): 6 hours at 20°C.

Usual number of coats: One.

Application method: Low pressure spray is best, brush or roller.

Clean up: Water when wet; mineral turps when dry.

Colour range: Clear.

Product ingredients will settle on storage. Shake well to reincorporate before use.

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. This material is quite bland; with vapour, occasional skin contact and even minor ingestion having negligible hazard. Repeated skin contact may, and any eye contact will, cause irritation. Harmful to aquatic life.

PRECAUTIONS

DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.

Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Avoid release to the environment.

FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation occurs get medical advice.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

Further information can be obtained from **AUST:** POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383. **NZ:** NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible on to newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways. See resene.com/cleanup for cleaning instructions.

Preparation

- Ensure the surface is in sound condition, dry and free from dirt, dust, loose material, oil (including mineral oil based wood finishes or similar) and salt.

- If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80). Flush clean with water.

- Remove accumulated windblown salt by washing with Resene Paint Prep and Housewash (see Data Sheet D812).

- If the surface you propose to treat is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller.

Application

- Resene Aquapel & Terracotta Sealer can only be used over a porous surface that will allow the treatment to penetrate. It cannot be applied over a fully sealed surface then overcoated.

- Saturate the surface with Resene Aquapel & Terracotta Sealer.

- When coating pots, coat the entire inside and outside of the pot.

- Remove any product that gets onto glass to avoid the risk of staining.

- If it starts to rain, immediately cease application and cover all treated areas that have yet to dry out.

- Maintain good ventilation throughout

the drying and curing period to ensure the treatment is properly cured. Poor ventilation may inhibit curing and performance.

- Maximum hydrophobicity (or water repellence) develops after a few days weathering.

- Dilute 2:1 with water when using as a clear finish over Resene FX Faux Rust Effect.

Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information. Please recycle.

For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Ltd
7 Production Ave, PO Box 918, Ashmore City, QLD 4214
Ph 1800 738 383, Visit resene.com.au

In New Zealand: Resene Paints Ltd
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045,
Ph (04) 577 0500, Visit resene.co.nz