Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase. Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project. LL82101 11/20

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children, Harmful if swallowed, Harmful if inhaled. Causes skin irritation. Causes serious eve irritation. Suspected of damaging fertility or the unborn child. May cause damage to organs. Toxic to aquatic life with long lasting effects.

PRECAUTIONS

DO NOT BREATHE MISTS, VAPOURS OR SPRAYS, DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Store locked up. Wear protective gloves and clothing, eye and face protection. Ground or bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting, intrinsically safe equipment. Avoid release to the environment. Obtain special instructions before use.

FIRST AID

IF SWALLOWED: Call a POISON CENTRE, doctor, physician or first aider if you feel unwell. IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation occurs get medical advice. Take off immediately all contaminated clothing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If exposed or concerned: call a POISON CENTRE.

If medical attention is required: have product container or label at hand.

Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363. CONTAINS: Toluene 610-800 gm/L

For cleaning of brushes/roller used for solventborne and waterborne paints.

SPILLS: Eliminate all sources of ignition. Ventilate area, avoid breathing vapours. Use absorbent clean-up materials, such as fire retardant treated sawdust or diatomaceous earth to dike and contain spill. Scrape up and remove. Collect and seal in properly labelled drums. Refer to local waste management authority. Keep out of public sewers and waterways.

IN CASE OF FIRE: Use foam, CO₂, dry chemical for extinction.





Brush Cleaner

net contents 1 litre

Recommended safety equipment

Safety glasses with side shields, protective clothing and gloves (neoprene or butyl rubber) should be worn when using this FLAMMABLE LIQUID product.

Directions

Protect skin and eves at all times with approved safety equipment.

- 1. If paint is still soft work Resene Brush Cleaner well into bristles or roller sleeve.
- 2 Rinse off in clean cold water
- 3. If a second treatment is required remove all water before applying Resene Brush Cleaner again.
- 4. Badly clogged brushes may require soaking overnight. Note some roller sleeves are not suitable to be soaked in solvents.

Place in a suitable solvent-proof container. Do not decant into plastic containers as the solvent will cause most

plastics to deteriorate rapidly. Cover bristles with Resene Brush Cleaner and fix lid or cover with oven foil. Leave 12-24 hours. Scrape through with a metal comb or wire brush and rinse out with clean cold water.

Be PaintWise

For tips on responsible disposal of paint cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted

UN NO. 1263 – PAINT paint and packaging. Or contact **RELATED MATERIAL**

vour Local Authority for disposal

HIGHLY FLAMMABLE LIQUID AND VAPOUR

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



the paint the professionals use

In Australia: Resene Paints (Aust) Limited 7 Production Ave, PO Box 924, Beenleigh, Old 4207 Ph 1800 738 383 Visit www.resene.com.au

In New Zealand: Resene Paints Limited Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045 Ph (04) 577 0500 Visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAI, an accredited certification body. Printed on environmentally responsible paper which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colou for the application of incorrect product to substrate or the <u>application</u> of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST). 0800 737 363 (NZ) or visit the Resene website

