

Landscape

waterborne timber & fence stain

exterior



net
contents
10 litres

LL31710108 11/19

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. May cause an allergic skin reaction.

PRECAUTIONS

AVOID BREATHING MIST, VAPOURS OR SPRAY.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Wear protective gloves, clothing, eye and face protection. Contaminated work clothing should not be allowed out of the workplace.

FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, first aider or physician if you feel unwell

IF ON SKIN (or hair): Rinse skin with plenty of soap and water. If skin irritation or rash occurs get medical advice or attention. Take off contaminated clothing and wash before reuse..

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

When seeking medical advice take this container with you. Further information can be obtained from
AUST: POISONS INFORMATION CENTRE 131 126
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)
or call Resene 0800 737 363.

For use as a decorative/protective coating.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums.

Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Crown Landscape is a waterborne stain designed to enhance, protect and rejuvenate exterior timber in landscaping, such as fences, retaining walls and decorative landscaping features.

Preparation

• Treatment with Resene Timber and Deck Wash (see Data Sheet D813) is recommended for all substrates to remove dirt, natural stains and enhance the degree of product penetration. Ensure substrates to be coated are in sound condition, dry, free from dirt, dust, loose material, salt, oil (including mineral oil based wood finishes or similar) and film forming stains/coatings..

• If mould/algae is present, treat with Resene Moss & Mould Killer (see Data Sheet D80).

• For repaints of existing penetrating stains remove any gross contamination and loose cellulose fibres. Complete removal of existing stain is required when the existing stain is film forming. Do not apply over mineral oil based wood finishes.

• **All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**

• Always colour test first to check your choice of Crown Landscape colour gives the result you want on the actual timber you are staining.

• Consult your Resene ColorShop or reseller for advice on coating severely weathered surfaces, exotic timbers, non-standard timbers and exterior doors and windows.

• This product may be used to stain a wide variety of surfaces. If the surface you propose to stain is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

Precautions

- Contains powerful fungicides to inhibit fungal growth.
- Avoid skin contact.
- Will not prevent checking of plywood.
- Where alkaline cleaners (including Resene Moss & Mould Killer) are used in the preparation of the substrate, ensure that any residue is removed by hosing down with clean water. These residues can affect film formation and, subsequently, durability.
- Trafficable areas coated with this product will not comply with the Building Act Clause D1.3.3(d).

Application

- Before use and regularly during use, stir well with a wide flat stirrer.
- Do not apply to film forming or mineral oil based stains.
- Do not allow the coating to pool in troughs or valleys.

- Apply one full coat and allow to dry before applying second coat if required.
- All faces of the timber should be treated with special attention to end grains.
- For new, dressed or dense timber allow to weather for 1-2 months.
- Will not penetrate through existing coatings or very hard latewood bands.
- For best results wipe excess Crown Landscape off with a dry, absorbent, lint-free cloth rubbing along the grain.
- Will typically require maintenance after two to three summers. Performance is related to the depth of colour applied. Light applications, light colours and dressed surfaces may require maintenance sooner, while heavier applications and darker colours will require less maintenance.

Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information.

Available in three colours:



Crown Landscape Black



Crown Landscape Cedar



Crown Landscape Kauri


Crown
PAINTS

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Ph 1800 738 383 Visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045
Ph (04) 577 0500 Visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAL, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

Quick Check

Use on: Exterior landscaping timber surfaces, such as fences, retaining walls and landscaping features.

Gloss level: Matt.

Typical coverage: Dressed timber: 1st coat, 12-14 square metres per litre, 2nd coat, 14-16 square metres per litre.

Badly weathered timber: 1st coat, 3-4 square metres per litre, 2nd coat 5-7 square metres per litre.

Dry time (minimum): 24 hours (dependent upon environment conditions). Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

Recoat time (minimum): 24 hours.

Primer required: No.

Usual number of coats: Two. Will require maintenance after two to three summers.

Application method: Brush, roller or spray.

Thinning and clean up: Do not thin. Clean up with water when wet or mineral turps when dry.

Before use: Stir well with a wide flat stirrer and also stir during application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. When using multiple packs of this product on the same project please mix them together before use. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

