

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.
Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. This material is quite bland; with vapour, occasional skin contact and even minor ingestion having negligible hazard. Repeated skin contact may, and any eye contact will, cause irritation. Harmful to aquatic life.

PRECAUTIONS & FIRST AID

Use with adequate ventilation. Do not eat, drink or smoke while using. Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods of cleaning equipment and disposing of unwanted paint. Do not contaminate any water supply. Avoid release to the environment.

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor or physician if you feel unwell.

IF ON SKIN OR HAIR: Rinse skin with plenty of soap and water. If skin irritation or rash occurs get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

IF INHALED: If breathing is difficult remove to fresh air and keep at rest in a position comfortable for breathing.

When seeking medical advice take this container with you. If exposed or concerned get medical advice or attention.

First Aid is not generally required. If in doubt, contact a POISONS INFORMATION CENTRE or a doctor. Further information can be obtained from AUS: POISONS INFORMATION CENTRE (131 126) or call Resene on 1800 738 383. NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene on 0800 737 363.

For use as a decorative/protective coating.

SPILLS

Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT

Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, not into outside stormwater drain where it may harm fish in local waterways.

KAREN WALKER

PAINTS

CHALK COLOUR WHITE

NET CONTENTS 1 LITRE

Tinter Included

Add colour, upcycle or rejuvenate walls, furniture, ceilings and accessories with matte Karen Walker Chalk Colour from Resene. We've combined Karen Walker's beautiful colour range with Resene's paint technology so you can bring out the best in your home with a luxurious matte finish. For most surfaces, simply wipe down and start painting – no priming, sanding or sealing needed. Depending on the look you want to create, apply 1–2 coats of Karen Walker Chalk Colour and finish with Karen Walker Soft Wax or Vintage Wax if you wish.

PREPARATION

For most surfaces, as long as the surface is clean, you can start painting. For surfaces with moss and mould, always treat this before you paint using Resene Moss & Mould Killer. If left untreated mould will grow through the new paint finish.

If you are working with a very smooth surface, such as varnished surfaces, high gloss enamels, laminates or tiles, for best long term results, wipe the surface clean and then apply Resene Waterborne Smooth Surface Sealer before applying your chosen Karen Walker Chalk Colour paint.

For already painted walls, make sure the walls are clean and then you can start painting. For new plasterboard walls, seal first with Resene Broadwall Wallboard Sealer, before applying Karen Walker Chalk Colour paint.

Stir the paint well with a wide flat stirrer before applying.

A primer or sealer may be required before applying Karen Walker Chalk Colour depending on the surface.

APPLICATION

Apply by brush, speed brush or roller. Usual coverage is 11 square metres per litre per coat. Most colours will need two coats, but

this will depend on the look you are trying to create. Bright colours may require an additional coat.

Dry time (minimum): 45 minutes. Apply when the temperature is over 10°C. Drying will be slower in a colder temperature and/or a high humidity. Recoat time (minimum): 2 hours. Clean up with water.

QUICK DRYING

To help the paint dry, open windows and if necessary use a fan to keep the air circulating.

For a smoother finish, add Resene Brushing Additive. This will give you more time to work with the paint.

SAVE WASH UP TIME

When you want to take a break, wrap your brush or roller in clear cling wrap. This will keep the paint and brush or roller moist and save you washing up time and effort.

COMPLEMENT WITH OTHER PRODUCTS

Karen Walker Chalk Colour is not recommended in wet areas or on trim and joinery – use Resene Lustacryl (semi-gloss) or Resene SpaceCote (low sheen or flat) instead to complement your Karen Walker Chalk Colour finish. Resene has a huge range of other paints and stains available to complement your new Karen Walker Chalk Colour finish. See www.resene.com for more details.

KEEPING IT CLEAN

You can wipe surfaces finished in Karen Walker Chalk Colour paint once they have been left to fully cure for a month. Clean using Resene Interior Paintwork Cleaner using the instructions on pack or in the Resene Caring for your Paint Finish brochure, available on the Resene website or at your local Resene ColorShop or reseller.

UNWANTED PAINT AND CANS

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your local authority for disposal information.

SHARE WITH US

We'd love to see your finished projects – please share them #karenwalkerchalk-colour or email to update@resene.co.nz.

Enjoy the Resene promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy. In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. When using multiple packs of this product on the same project please mix them together before use. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause standard results or system failure. For further painting advice and information call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld, 4207
Ph 1800 738 383 visit www.resene.com.au
In New Zealand: Resene Paints Limited
Vogel St, PO Box 38242,
Wgtn Mail Centre, Lower Hutt 5045
Ph (04) 577 0500 visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAI, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

LL1410201 10/19

