Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase. Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best guality finish for your specific project.



<u>esene</u> **Quick2Clean Paint Equipment** net contents 1 litre designed for spray equipment and as a brush conditioner for waterborne paints

net contents 1 litre 118468901B 11/23

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Causes skin irritation. Cause's serious eye damage. Toxic to aquatic life with long lasting effects.

PRECAUTIONS

DO NOT EAT. DRINK OR SMOKE WHEN USING THIS PRODUCT

Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Wear protective gloves and clothing, eye and face protection. Wash all exposed external body areas thoroughly after handling. Avoid release to the environment.

FIRST AID

IF SWALLOWED: Rinse mouth, Do NOT induce vomiting, Call a POISON CENTRE, doctor or first aider if you feel unwell. IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTRE, doctor or first aider if you feel unwell. IF ON SKIN (or hair): Wash with plenty of water. If skin irritation occurs get medical advice or attention. Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention

Further information can be obtained from AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363

If medical advice is needed: have product container at hand. CONTAINS: Sodium Dioctyl Sulfosuccinate 10-110 g/L. For use as a cleaner

For full technical instructions see Data Sheet D818

Resene Quick2Clean Paint Equipment is designed to make 2. Rinse off in clean cold water. All residues must be removed (e.g. no cleaning spray equipment quick and easy to help you maintain foaming when the wet roller sleeve is vigorously rubbed) to prevent and maximise the life of your spray gear. It is also suitable as application problems. a conditioner for brushes used with waterborne paints to help 3. If a second treatment is required remove as much water as possible vou care for your brushes.

How to use

Protect skin and eyes at all times with approved safety equipment.

Spray equipment

For best results, follow these steps:

1. Flush your unit with water to remove paint from the unit and hose. 2. Drop the pressure and remove all filters. Clean them with correctly diluted Resene Quick2Clean Paint Equipment and store them safely in your toolbox

3. Put the unit back together without the filters. Clean excess paint off the pick-up shaft with correctly diluted Resene Quick2Clean Paint Equipment. 4. Remove the dirty water and replace with a bucket of fresh water, using warm if possible. Add 2 capfuls of Resene Quick2Clean Paint Equipment to 5 litres of warm water. Flush through the unit until clean.

5. Mix a small amount of fresh water in a bucket with Resene Pump Protector. Run through your unit.

6. Drop the pressure and store your unit.

7. BADLY CLOGGED HOSES AND OR FILTERS MAY REOUIRE REPLACEMENT.

For brushes/rollers used with waterborne paints 1. If paint is still soft, work diluted Resene Quick2Clean Paint Equipment well into the bristles/roller sleeve

In Australia: Resene Paints (Aust) Limited 7 Production Ave. PO Box 918. Ashmore City, OLD 4214 Ph 1800 738 383 Visit resene com au

the paint the professionals use

In New Zealand: Resene Paints Ltd Vogel St. PO Box 38242. Watn Mail Centre. Lower Hutt 5045 Ph 04 577 0500 Visit resene.co.nz

before repeating Step 1.

4. Badly clogged brushes may require soaking overnight in Resene Brush Cleaner. Place in a suitable solvent-proof container. Cover bristles/sleeve with Resene Brush Cleaner and cover with oven foil or a wet rag. Leave 12-24 hours. Scrape through with a metal comb or wire brush and repeat steps 1 and 2.

Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information. Please recycle.

Please ensure that use of this product is compatible with the equipment being cleaned. Resene does not accept any responsibility for the use of incorrect product. Read the appropriate Data Sheet and Safety Data Sheet before

Quick2Clean Pain Quick2Clean Pain Equipment SDS Equipment TDS

Ouick check

Use on: Spray equipment, brushes, roller sleeves

Appearance: Hazy pale orange/yellow liquid

Mixing ratio: Add 2 capfuls of Resene Quick2Clean Paint Equipment to 5 litres of warm water. One capful = 15 mL. No. of applications: Usually one. Badly clogged paint equipment may need a second application or may require replacement.

Clean up: Water.

