

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase. Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

Resene

Aquaclear Natural

waterborne clear

interior

WARNING

KEEP OUT OF REACH OF CHILDREN



9 418022 074113

FLAT

net
contents
1 litre

LL2420001F 8-24

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

PRECAUTIONS

USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.

Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Wear protective gloves and clothing, eye and face protection. Wash all exposed external body areas thoroughly after handling. Avoid release to the environment.

FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation occurs get medical advice.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

When seeking medical advice take this container with you.

Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D59.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways. See resene.com/cleanup for cleaning instructions.

Quick check

Use on: Interior timber walls and ceilings.

Gloss level: Flat natural. Resene Aquaclear Satin, Semi-Gloss and Gloss are also available for interior timber surfaces.

Coverage (average): 10-12 square metres per litre per coat. Spreading rates are given for bare timber - take care not to overspread on sealed surfaces.

Dry time (minimum): 30 minutes at 20°C. Allow 72 hours for coating to reach full cure. Do not apply at temperatures below 10°C or when temperatures are liable to drop below this during the drying period. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

Recoat time (minimum): 2 hours at 20°C.

Primer required: No.

Usual number of coats: Three - minimum. Apply an additional coat in areas prone to higher wear and tear.

Application method: Roller (Resene No.4 roller sleeve), spray, speed brush or synthetic bristle brush.

Thinning and clean up: Water. Thin the first coat with up to 10% clean water.

In hot and dry conditions: Application is difficult at high temperatures and low humidity. Add up to 5% Resene Hot Weather Additive.

Colour range: Milky - dries clear.

Before use: Stir well with a wide flat stirrer.



Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

Read the appropriate Product Data Sheet and Safety Data Sheet before use.

Resene Aquaclear Natural is a waterborne clear flat finish for interior timber walls and ceilings, designed to enhance and protect timber from everyday wear and tear. Use with Resene Colour Enhance to add extra depth and colour to timber.

Preparation

- Ensure the surface is in sound condition, dry and free from dirt, dust, loose material, oil and grease.
- If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80).
- Stop all nail holes and cracked timber with a suitable filler.
- Thoroughly sand surfaces prior to coating. Finish off with fine sandpaper, sanding with the grain. Remove all sanding dust.
- Sand previously varnished surfaces to remove all gloss and provide a key for good adhesion. Wipe off sanding dust. If old varnish is flaking everything must

be removed to ensure a uniform appearance.

• **All sanding dusts can be harmful. Always wear appropriate protection. Seek expert advice if working with lead, chromate or asbestos based materials or surfaces.**

- This product may be used to coat a wide variety of surfaces. If the surface you propose to coat is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

Application

- For uncoated surfaces thin first coat up to 10% with clean water.
- Stir thoroughly with a wide flat stirrer before and during use.
- Apply with a speed brush, synthetic bristle brush, roller (Resene No.4 roller sleeve) or spray, allowing dry time between coats. Apply evenly. Avoid working over a surface that has begun to set as this will give a patchy appearance.

- Do not brush or roll excessively to avoid foaming.
- Do not apply in direct sunlight.
- Maintain good ventilation throughout the drying and post application curing period to ensure the paint is properly cured. This may require use of an extraction system when painting in marginal painting conditions. Do not use gas or diesel burners to heat the coated area as these produce water that will inhibit drying and curing. Poor ventilation may affect appearance and performance.

Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information. Please recycle.

Please ensure that use of this product is compatible with the substrate and surface preparation method. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.



Aquaclear SDS



Aquaclear TDS

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Ltd
7 Production Ave, PO Box 918, Ashmore City, QLD 4214
Ph 1800 738 383 Visit resene.com.au

In New Zealand: Resene Paints Ltd
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045
Ph (04) 577 0500 Visit resene.co.nz