

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.
Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

net contents 1 litre
tint included

LL2241901 7-24

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May cause damage to organs through prolonged or repeated exposure. May damage fertility or the unborn child. Harmful to aquatic life with long lasting effects.

PRECAUTIONS

DO NOT BREATHE THE MIST, VAPOURS OR SPRAY. DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.

Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Store locked up. Wear protective gloves and clothing, eye and face protection. Wash all exposed external body areas thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and intrinsically safe equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid release to the environment. Obtain special instructions before use.

FIRST AID

IF SWALLOWED: Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF ON SKIN (or hair): Wash with plenty of water. If skin irritation or rash occurs get medical advice or attention. Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical attention or advice.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing breathing difficulties immediately seek medical attention.

If exposed or concerned get medical attention or advice.

If medical attention is required have product container or label at hand. Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126

or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)

or call Resene 0800 737 363.

CONTAINS: Naphtha Petroleum, light aromatic Solvent 180-380 g/L.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D57.

If exposed or concerned get medical attention.

SPILLS: Use appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with Resene Brush Cleaner or mineral turps. Do not allow mineral turps to enter any drains. Refer to your local Council for disposal of dirty mineral turps. See resene.com/cleanup for cleaning instructions.

FIRE: Use foam, carbon dioxide or dry chemical powder.

DANGER

KEEP OUT OF REACH OF CHILDREN

Resene

Woodsman Wood Oil Stain

exterior



9 418022 1004035 1

TINT
BASE

Resene Woodsman Wood Oil Stain is a solventborne wood oil stain matching the needs of timber with your desire to achieve the most natural appearance possible. Use on exterior timber including trafficable areas such as decks.

Preparation

• Ensure the surface is in sound condition, dry and free from dirt, dust, loose material, oil (including mineral oil based wood finishes or similar) and salt.

• Treat timber with Resene Timber and Deck Wash (see Data Sheet D813) to remove dirt, natural stains and enhance the degree of product penetration.

• Remove accumulated windblown salt by washing with Resene Paint Prep and Housewash (see Data Sheet D812).

• If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80).

• Thoroughly sand any bare timber surface that has been left exposed to the weather for more than one week.

• For repaints of existing penetrating stains remove any gross contamination and loose cellulose fibres.

• **All sanding dusts can be harmful. Always wear appropriate protection. Seek expert advice if working with lead, chromate or asbestos based materials or surfaces.**

• Always colour test first to see your choice of Resene Woodsman Wood Oil Stain colour gives the result you want on the actual timber you are coating.

• Consult your Resene ColorShop or reseller on coating severely weathered surfaces, exotic timbers, non-standard timbers and exterior doors and windows.

• Do not use wood oil stains for substrates that will be used in the collection of rainwater for drinking purposes.

• This product may be used on a wide variety of surfaces. If the surface you propose to stain is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

• Do not use wood oil stains for substrates that will be used in the collection of rainwater for drinking purposes.

• This product may be used on a wide variety of surfaces. If the surface you propose to stain is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

• Do not use wood oil stains for substrates that will be used in the collection of rainwater for drinking purposes.

• This product may be used on a wide variety of surfaces. If the surface you propose to stain is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

• Do not use wood oil stains for substrates that will be used in the collection of rainwater for drinking purposes.

• This product may be used on a wide variety of surfaces. If the surface you propose to stain is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

• Do not use wood oil stains for substrates that will be used in the collection of rainwater for drinking purposes.

• This product may be used on a wide variety of surfaces. If the surface you propose to stain is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

• Do not use wood oil stains for substrates that will be used in the collection of rainwater for drinking purposes.

• This product may be used on a wide variety of surfaces. If the surface you propose to stain is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

• Do not use wood oil stains for substrates that will be used in the collection of rainwater for drinking purposes.

• This product may be used on a wide variety of surfaces. If the surface you propose to stain is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

• Do not use wood oil stains for substrates that will be used in the collection of rainwater for drinking purposes.

• This product may be used on a wide variety of surfaces. If the surface you propose to stain is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

• Do not use wood oil stains for substrates that will be used in the collection of rainwater for drinking purposes.

• This product may be used on a wide variety of surfaces. If the surface you propose to stain is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

• Will typically require maintenance after two summers. Performance is related to the depth of colour applied. Light applications, light colours and dressed surfaces may require maintenance sooner, while heavier applications, darker colours and rough sawn surfaces will require less maintenance.

Precautions

• Trafficable areas coated with this unmodified product will not comply with the Building Act Clause D1.3.3(d).

Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information. Please recycle.



UN NO. 1263 –
PAINT RELATED
PRODUCT



Woodsman Wood
Oil Stain SDS

Resene
the paint the professionals use



Woodsman Wood
Oil Stain TDS

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 918, Ashmore City, QLD 4214
Ph 1800 738 383 Visit resene.com.au

In New Zealand: Resene Paints Limited
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045
Ph (04) 577 0500 Visit resene.co.nz

Quick check

Use on: Exterior timber surfaces.

Gloss level: None. Fully penetrating.

Typical coverage:

(a) Dressed timber: 1st coat, 10-12 square metres per litre; 2nd coat, 12-14 square metres per litre; apply a 3rd coat, 12-14 square metres per litre after 3-6 months.

(b) Rough sawn timber: 1st coat, 4-6 square metres per litre; 2nd coat, 9-11 square metres per litre.

(c) Badly weathered timber: 1st coat, 3-4 square metres per litre; 2nd coat 5-7 square metres per litre.

Dry time (minimum): 24 hours at 20°C. Drying is slowed by low temperatures and high humidity.

Recoat time (minimum): 24 hours at 20°C.

Primer required: No.

Usual number of coats: Two. Will require maintenance after two summers.

Application method: Brush, roller or spray.

Thinnin: Do not thin.

Clean up: Mineral turps.

Colour range: Selected colours from the Resene Exterior woodcare colour chart.

Also available as Resene Woodsman CoolColour to help reflect heat from exterior surfaces. Application of a Resene CoolColour will reflect more heat than the same colour made using non-cool pigmentation and reduce heat related stress on the substrate; it will not make the stained surface cool to touch. Check with Resene staff whether a Resene CoolColour is right for your project.

Before use: Stir well with a wide flat stirrer and also stir during application.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

Read the appropriate Product Data Sheet and Safety Data Sheet before use.

FLAMMABLE LIQUID AND VAPOUR
Keep away from heat, sparks, open flames
and hot surfaces. No smoking.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. When using multiple packs of this product on the same project please mix them together before use. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.