

net contents 800 mL Makes 4L when mixed with 3.2L of

FX Write-on Wall Paint PART A

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Causes mild skin irritation. May cause an allergic skin reaction. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Causes damage to organs through prolonged or repeated exposure. Harmful to aquatic life.

LL1379901B 5/23

PRECAUTIONS

DO NOT BREATHE DUST, FUMES, GAS, MIST, VAPOURS OR SPRAY, DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT. Store in original or correctly labelled container, tightly closed, in a wellventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Wear protective gloves and clothing, eye

and face protection. Use only outdoors or in a well-ventilated area. In case of inadequate ventilation wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment.

FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation occurs get medical advice. Wash contaminated clothing before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms call a POISON CENTRE, doctor or first aider.

If exposed or concerned get medical attention. When seeking medical advice take this container with you.

Call a POISON CENTRE, doctor or physician if you feel unwell. Further information can be obtained from AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383. NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363. CONTAINS: Hexamethylene Diisocvanate 1-5 o/L.

SPILLS: Use appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with Resene Brush Cleaner or mineral turps. Do not allow mineral turps to enter any drains. Refer to your local Council for disposal of dirty mineral turps.

FIRE: Use foam, carbon dioxide or dry chemical powder.

BE PAINTWISE: For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging.Or contact your Local Authority for disposal information. Please recycle.









Write on your walls with whiteboard markers without damaging the surface with Resene FX Write-on Wall Paint, a two-component waterborne clear coating designed to produce a whiteboard effect over previously painted or sealed substrates. Use only with high quality whiteboard markers using a whiteboard eraser or soft cloth to clean. Over a darker paint finish use high quality liquid chalk.

Instructions for use:

Refer to Resene FX Write-on Wall Paint application and use instructions for instructions on preparation, mixing, application and use.

Permanent markers will not rub off the coating using rags or whiteboard erasers but they will not damage the coating. Use methylated spirits or other cleaning fluids to remove permanent markers. Occasional use of methylated spirits for cleaning will not damage the coating.

Please ensure that use of this product is compatible with the substrate and surface preparation method. Resene does not accept any responsibility for the <u>application</u> of incorrect product to substrate or the <u>application</u> of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy. In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.



COMBUSTIBLE LIQUID Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.





the paint the professionals use

In Australia: Resene Paints (Aust) Limited 7 Production Ave, PO Box 918, Ashmore City, QLD 4214 Ph 1800 738 383 Visit resene.com.au

In New Zealand: Resene Paints Limited Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045 Ph (04) 577 0500 Visit resene.co.nz