

Resene Deep Clean

path, patio and deck care

Resene Deep Clean is the simple, safe method of keeping all your outdoor areas free from moss, mould, algae and lichen. Simply spray or brush on and leave Resene Deep Clean and nature to do the work. Slow acting Resene Deep Clean gets right down to the roots of the problem, destroying the growth and combining with nature to let the remains be weathered off leaving a cleaner surface.

exterior

Typical uses

- Decks
- Paths
- Patios
- Other exterior cementitious, timber and painted surfaces

	Physical properties
Type	Blended surfactants and cleansers
Form	Aqueous solution
Solvent	Water
Solution viscosity	Water thin
Colour	Colourless
Dilution	One part Resene Deep Clean to four parts freshwater
VOC	97 grams per litre Dipropylene Glycol Monomethyl Ether (see Resene VOC Summary)

Performance and limitations

- Performance**
1. Easy to apply, with no scrubbing needed.
 2. Works slowly over time to provide a longer lasting cleaning effect.
 3. Helps maintain the longevity of the paint finish or surface.
 4. Reduces the risk of slipping in trafficable areas.

- Limitations**
1. Do not add Deep Clean to paint.
 2. Mild steel and aluminium are attacked by Resene Deep Clean and are unsuitable materials for either storage or application equipment.
 3. Ensure product is well rinsed off glass surfaces. Concentrated product left on glass surfaces may etch the surface.
 4. Avoid use on windy days and wet days as it will be difficult to control the spray and ensure that the surface is fully wetted with Resene Deep Clean.

Deep Clean

Application

Wear adequate protection. Use overalls, gloves, eye protection and suitable footwear.

Mix Resene Deep Clean with water and apply by brush or low pressure spray to saturate the surface. Porous surfaces must be fully wetted to ensure the best result is achieved. Leave the solution to soak in – do not rinse off. It may take up to one week to see any visible effect on lichen, mould and algae.

Areas suffering from heavy growth may require further application.

Thoroughly clean the application tool or spray equipment with freshwater immediately after use. Do not store concentrated or diluted product in metal or aluminium containers.

Where possible avoid contact with plants (see limitations) but if contact does occur wash plants with copious quantities of freshwater as soon after contact as is practical. Do not allow diluted product to dry on plants.

When treating lichen, ensure surface is dry, spot spray lichen and leave for 15-30 minutes. Then apply Resene Deep Clean to the whole area.

For an immediate exterior clean use Resene Paint Prep and Housewash (see [Data Sheet D812](#)).

Precautions

Do not allow the product to come into contact with plants, stormwater outlets, streams or animals. May kill aquatic life if allowed to enter the stormwater system. Divert all roof run-off to a sewer or alternative catchment system.

*Please ensure the current Data Sheet is consulted prior to specification or application of Resene products.
If the surface you propose to coat is not referred to by this Data Sheet, please contact Resene for clarification.*

In Australia
PO Box 924, Beenleigh, Qld 4207
Call 1800 738 383, visit www.resene.com.au
or email advice@resene.com.au

Resene
the paint the professionals use

In New Zealand
PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Call 0800 RESENE (737 363), visit www.resene.co.nz
or email advice@resene.co.nz