

RESENE LIMELOCK

Resene Paints LTD

Version No: 1.1

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Issue Date: 15/06/2022

Print Date: 15/06/2022

L.GHS.NZL.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	RESENE LIMELOCK
Synonyms	Not Available
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	11175
--------------------------	-------

Details of the supplier of the safety data sheet

Registered company name	Resene Paints LTD
Address	32-50 Vogel Street Wellington 5011 New Zealand
Telephone	+64 4 5770500
Fax	+64 4 5773327
Website	www.resene.co.nz
Email	advice@resene.co.nz

Emergency telephone number

Association / Organisation	NZ POISONS (24hr 7days)	CHEMWATCH EMERGENCY RESPONSE
Emergency telephone numbers	0800 764766	+64 800 700 112
Other emergency telephone numbers	Not Available	+61 3 9573 3188

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

Classification [1]	Specific Target Organ Toxicity - Repeated Exposure Category 2
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	6.9B

Label elements

Hazard pictogram(s)	
---------------------	---

Signal word	Warning
-------------	---------

Hazard statement(s)

H373	May cause damage to organs through prolonged or repeated exposure. (Inhalation)
------	---

Precautionary statement(s) Prevention

P260	Do not breathe mist/vapours/spray.
------	------------------------------------

Precautionary statement(s) Response

P314	Get medical advice/attention if you feel unwell.
------	--

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

RESENE LIMELOCK

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
-------------	--

Not Applicable

SECTION 3 Composition / information on ingredients**Substances**

See section below for composition of Mixtures

Ingredients are required by the Hazard Substances (Safety Data Sheets) Notice 2017, EPA consolidation 30 April 2021 to be identified:

Mixtures

CAS No	%[weight]	Name
112-34-5	1-5	<u>diethylene glycol monobutyl ether</u>
84133-50-6	0.1-0.5	<u>alcohols C12-14 secondary ethoxylated</u>
Legend:		
1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; * EU IOELVs available		

SECTION 4 First aid measures**Description of first aid measures**

Eye Contact	<p>If this product comes in contact with eyes:</p> <ul style="list-style-type: none"> ▶ Wash out immediately with water. ▶ If irritation continues, seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none"> ▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area. ▶ Other measures are usually unnecessary.
Ingestion	<ul style="list-style-type: none"> ▶ Immediately give a glass of water. ▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures**Extinguishing media**

- ▶ There is no restriction on the type of extinguisher which may be used.
- ▶ Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
-----------------------------	-------------

Advice for firefighters

Fire Fighting	▶ Alert Fire Brigade and tell them location and nature of hazard.
Fire/Explosion Hazard	<ul style="list-style-type: none"> ▶ Non combustible. ▶ May emit poisonous fumes. ▶ May emit corrosive fumes.

SECTION 6 Accidental release measures**Personal precautions, protective equipment and emergency procedures**

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	<ul style="list-style-type: none"> ▶ Clean up all spills immediately. <p>Control personal contact with the substance, by using personal protective equipment. Contain spill with sawdust, sand, earth, inert material or vermiculite then place in suitable, labelled container for waste disposal. Wipe up. Clean area with large quantity of water to complete clean- up.</p>
Major Spills	<p>Moderate hazard.</p> <p>Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear appropriate personnel protective equipment and clothing to prevent exposure. Avoid breathing in mists or vapours and skin or eyes contact. Prevent, by any means available,</p>

Continued...

RESENE LIMELOCK

spillage from entering drains or water course. Stop leak if safe to do so. Contain spill with sawdust, sand, earth, inert material or vermiculite then place in suitable, labelled container for waste disposal. Wipe up. Wash area and prevent runoff into drains. If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	<ul style="list-style-type: none"> ▶ Avoid unnecessary personal contact, including inhalation. ▶ DO NOT allow clothing wet with material to stay in contact with skin
Other information	

Conditions for safe storage, including any incompatibilities

Suitable container	▶ As supplied by manufacturer
Storage incompatibility	Strong oxidisers

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
diethylene glycol monobutyl ether	30 ppm	33 ppm	200 ppm

Ingredient	Original IDLH	Revised IDLH
diethylene glycol monobutyl ether	Not Available	Not Available
alcohols C12-14 secondary ethoxylated	Not Available	Not Available

Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
diethylene glycol monobutyl ether	E	≤ 0.1 ppm
alcohols C12-14 secondary ethoxylated	E	≤ 0.1 ppm

Notes:

Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

MATERIAL DATA


For diethylene glycol monobutyl ether:

CEL TWA: 15.5 ppm, 100 mg/m³

(CEL = Chemwatch Exposure Limit)

In studies involving the inhalation toxicity of diethylene glycol monobutyl ether, exposure for 6 hours daily at 100 mg/m³ had no effect.

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard.
Personal protection	
Eye and face protection	▶ Safety glasses with side shields.
Skin protection	See Hand protection below
Hands/feet protection	▶ Wear chemical protective gloves, e.g. PVC. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer.
Body protection	Overalls
Respiratory protection	Not required for properly ventilated areas. Where the concentration of vapours in the breathing zone approaches or exceeds the "Exposure Standards" respiratory protection is required. Type A Filter of sufficient capacity.

Continued...

RESENE LIMELock

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	White acrylic dispersion		
Physical state	Liquid	Relative density (Water = 1)	1.12
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	8-9	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	700-1000
Initial boiling point and boiling range (°C)	100	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	55
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (Not Available%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	60.1

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	▶ stable
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models).
Ingestion	The material has NOT been classified by EC Directives or other classification systems as 'harmful by ingestion'.
Skin Contact	Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects.
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Repeated or long-term occupational exposure by inhalation is likely to produce cumulative health effects involving organs.

RESENE LIMELock	TOXICITY	IRRITATION
	Not Available	Not Available

RESENE LIMELock

diethylene glycol monobutyl ether	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 4120 mg/kg ^[2]	Eye (rabbit): 20 mg/24h moderate
	Oral (Rat) LD50; 5660 mg/kg ^[2]	Eye (rabbit): 5 mg - SEVERE
alcohols C12-14 secondary ethoxylated	TOXICITY	IRRITATION
	Not Available	Not Available
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

DIETHYLENE GLYCOL MONOBUTYL ETHER	<p>The material may produce severe irritation to the eye causing pronounced inflammation.</p> <p>For diethylene glycol monoalkyl ethers and their acetates: This category includes diethylene glycol ethyl ether (DGEE), diethylene glycol propyl ether (DGPE) diethylene glycol butyl ether (DGBE) and diethylene glycol hexyl ether (DGHE) and their acetates.</p> <p>Acute toxicity: There are adequate oral, inhalation and/or dermal toxicity studies on the category members.</p>
ALCOHOLS C12-14 SECONDARY ETHOXYLATED	<p>No significant acute toxicological data identified in literature search.</p> <p>Polyethers, for example, ethoxylated surfactants and polyethylene glycols, are highly susceptible towards air oxidation as the ether oxygens will stabilize intermediary radicals involved.</p> <p>Human beings have regular contact with alcohol ethoxylates through a variety of industrial and consumer products such as soaps, detergents, and other cleaning products .</p> <p>Alcohol ethoxylates are according to CESIO (2000) classified as Irritant or Harmful depending on the number of EO-units: EO < 5 gives Irritant (Xi) with R38 (Irritating to skin) and R41 (Risk of serious damage to eyes) EO > 5-15 gives Harmful (Xn) with R22 (Harmful if swallowed) - R38/41 EO > 15-20 gives Harmful (Xn) with R22-41 >20 EO is not classified (CESIO 2000) Oxo-AE, C13 EO10 and C13 EO15, are Irritating (Xi) with R36/38 (Irritating to eyes and skin) . AE are not included in Annex 1 of the list of dangerous substances of the Council Directive 67/548/EEC</p> <p>In general, alcohol ethoxylates (AE) are readily absorbed through the skin of guinea pigs and rats and through the gastrointestinal mucosa of rats.</p> <p>For high boiling ethylene glycol ethers (typically triethylene- and tetraethylene glycol ethers): Skin absorption: Available skin absorption data for triethylene glycol ether (TGBE), triethylene glycol methyl ether (TGME), and triethylene glycol ethylene ether (TGEE) suggest that the rate of absorption in skin of these three glycol ethers is 22 to 34 micrograms/cm2/hr, with the methyl ether having the highest permeation constant and the butyl ether having the lowest.</p>

Acute Toxicity	✗	Carcinogenicity	✗
Skin Irritation/Corrosion	✗	Reproductivity	✗
Serious Eye Damage/Irritation	✗	STOT - Single Exposure	✗
Respiratory or Skin sensitisation	✗	STOT - Repeated Exposure	✓
Mutagenicity	✗	Aspiration Hazard	✗

Legend: ✗ – Data either not available or does not fill the criteria for classification
✓ – Data available to make classification

SECTION 12 Ecological information

Toxicity

RESENE LIMELock	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
diethylene glycol monobutyl ether	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	1101mg/l	2
	NOEC(ECx)	96h	Algae or other aquatic plants	>=100mg/l	1
	EC50	48h	Crustacea	>100mg/l	1
	EC50	96h	Algae or other aquatic plants	>100mg/l	1
	LC50	96h	Fish	1300mg/l	2
alcohols C12-14 secondary ethoxylated	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

DO NOT discharge into sewer or waterways.

Persistence and degradability

Continued...

RESENE LIMELock

Ingredient	Persistence: Water/Soil	Persistence: Air
diethylene glycol monobutyl ether	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
diethylene glycol monobutyl ether	LOW (BCF = 0.46)

Mobility in soil

Ingredient	Mobility
diethylene glycol monobutyl ether	LOW (KOC = 10)

SECTION 13 Disposal considerations**Waste treatment methods**

Product / Packaging disposal	<p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory.</p> <ul style="list-style-type: none"> ▶ DO NOT allow wash water from cleaning or process equipment to enter drains. ▶ Recycle wherever possible. <p>Consult manufacturer for recycling option.</p> <p>Resene Paintwise accepts residual unwanted paint and packaging. See Resene website for Paintwise information. Or contact a Local Authority for the disposal information. Do not discharge the substance into the environment.</p>
-------------------------------------	---

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package.

Do not allow product or wash water from cleaning or process equipment to enter drains or watercourses. It may be necessary to collect all wash water for treatment before disposal. The generation of waste should be avoided or minimised wherever possible.

Disposal of this product should comply with Hazard Substances (Disposal) Notice 2017 (EPA Consolidation 30 April 2021).

For treating and discharging processes contact your local authority.

SECTION 14 Transport information**Labels Required**

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
diethylene glycol monobutyl ether	Not Available
alcohols C12-14 secondary ethoxylated	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
diethylene glycol monobutyl ether	Not Available
alcohols C12-14 secondary ethoxylated	Not Available

SECTION 15 Regulatory information**Safety, health and environmental regulations / legislation specific for the substance or mixture**

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002670	Surface Coatings and Colourants Subsidiary Hazard Group Standard 2020

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

Continued...

RESENE LIMELOCK

diethylene glycol monobutyl ether is found on the following regulatory lists

New Zealand Approved Hazardous Substances with controls
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
New Zealand Inventory of Chemicals (NZIoC)

alcohols C12-14 secondary ethoxylated is found on the following regulatory lists

New Zealand Approved Hazardous Substances with controls
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
New Zealand Inventory of Chemicals (NZIoC)

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantities
Not Applicable	Not Applicable

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
New Zealand - NZIoC	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	15/06/2022
Initial Date	14/06/2022

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment.

Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average
PC—STEL: Permissible Concentration-Short Term Exposure Limit
IARC: International Agency for Research on Cancer
ACGIH: American Conference of Governmental Industrial Hygienists
STEL: Short Term Exposure Limit
TEEL: Temporary Emergency Exposure Limit.
IDLH: Immediately Dangerous to Life or Health Concentrations
ES: Exposure Standard
OSF: Odour Safety Factor
NOAEL :No Observed Adverse Effect Level
LOAEL: Lowest Observed Adverse Effect Level
TLV: Threshold Limit Value
LOD: Limit Of Detection
OTV: Odour Threshold Value
BCF: BioConcentration Factors
BEI: Biological Exposure Index
AIIC: Australian Inventory of Industrial Chemicals
DSL: Domestic Substances List
NDSL: Non-Domestic Substances List
IECSC: Inventory of Existing Chemical Substance in China
EINECS: European INventory of Existing Commercial chemical Substances
ELINCS: European List of Notified Chemical Substances
NLP: No-Longer Polymers
ENCS: Existing and New Chemical Substances Inventory
KECI: Korea Existing Chemicals Inventory

RESENE LIMELock

NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act

TCSI: Taiwan Chemical Substance Inventory

INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.