RESENE SQUASH COURT COATING BASE

Resene Paints Ltd

Version No: 2.2

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Issue Date: **08/04/2022** Print Date: **08/04/2022** L.GHS.NZL.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier Product name RESENE SQUASH COURT COATING BASE Synonyms Not Available Other means of identification Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	9102

Details of the supplier of the safety data sheet

	•
Registered company name	Resene Paints Ltd
Address	32-50 Vogel Street Wellington New Zealand
Telephone	+64 4 577 0500
Fax	+64 4 5773327
Website	www.resene.co.nz
Email	advice@resene.co.nz

Emergency telephone number

Association / Organisation	NZ POISONS (24hr 7 days)	CHEMWATCH EMERGENCY RESPONSE
Emergency telephone numbers	0800 764766	+64 800 700 112
Other emergency telephone numbers	Not Available	+61 2 9186 1132

Once connected and if the message is not in your prefered language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

Classification ^[1]	Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 2, Sensitisation (Skin) Category 1, Hazardous to the Aquatic Environment Long-Term Hazard Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	6.3A, 6.4A, 6.5B (contact), 9.1C

Label elements

Hazard pictogram(s)



Signal word	Warning
-------------	---------

Hazard statement(s)

4.7	
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statement(s) Prevention

P280	Wear protective gloves, protective clothing, eye protection and face protection.
P261	Avoid breathing mist/vapours/spray.
P273	Avoid release to the environment.
P264	Wash all exposed external body areas thoroughly after handling.

Version No: **2.2** Page **2** of **9** Issue Date: **08/04/2022**

RESENE SQUASH COURT COATING BASE

Print Date: 08/04/2022

P272 Contaminated work clothing should not be allowed out of the workplace.

Precautionary statement(s) Response

P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Ingredients are required by the Hazard Substances (Safety Data Sheets) Notice 2017, EPA consolidation 30 April 2021 to be identified:

Mixtures

CAS No	%[weight]	Name
68131-40-8	0.36	alcohols C11-15 secondary ethoxylated
1477-55-0	0.1-1	m-xylenediamine
2855-13-2	0.1-1	isophorone diamine
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available	

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Transport to hospital or doctor if irritation occurs.
Skin Contact	If skin or hair contact occurs: Remove all contaminated clothing, including footwear. Wash skin and hair with running water Transport to hospital, or doctor if irritation occurs.
Inhalation	▶ Remove from contaminated area.
Ingestion	 For advice, contact a Poisons Information Centre or a doctor at once. If swallowed doNOT induce vomiting. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.	
Advice for firefighters		
Fire Fighting	Alert Fire Brigade and tell them location and nature of hazard.	
Fire/Explosion Hazard	► Non combustible. May emit poisonous fumes. May emit corrosive fumes.	

Version No: **2.2** Page **3** of **9** Issue Date: **08/04/2022**

RESENE SQUASH COURT COATING BASE

Print Date: 08/04/2022

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Control personal contact with the substance, by using personal protective equipment. Contain spill with sawdust, sand, earth, inert material or vermiculite then place in suitable, labelled container for waste disposal. Wipe up. Clean area with large quantity of water to complete clean- up.
Major Spills	Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear appropriate personnel protective equipment and clothing to prevent exposure. Avoid breathing in mists or vapours and skin or eyes contact. Prevent, by any means available, spillage from entering drains or water course. Stop leak if safe to do so. Contain spill with sawdust, sand, earth, inert material or vermiculite then place in suitable, labelled container for waste disposal. Wipe up. Wash area and prevent runoff into drains. If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	Avoid unnecessary personal contact, including inhalation.
Other information	

Conditions for safe storage, including any incompatibilities

Suitable container	As supplied by manufacturer.
Storage incompatibility	None known

SECTION 8 Exposure controls / personal protection

TEEL-1

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	m-xylenediamine	m-Xylene a,a'-diamine	Not Available	Not Available	0.1 mg/m3	(skin)-Skin absorption

TEEL-2

TEEL-3

Emergency Limits

Ingredient

RESENE SQUASH COURT COATING BASE	Not Available Not Available			Not Available
Ingredient	Original IDLH		Revised IDLH	
alcohols C11-15 secondary ethoxylated	Not Available		Not Available	
m-xylenediamine	Not Available		Not Available	
isophorone diamine	Not Available		Not Available	

Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
alcohols C11-15 secondary ethoxylated	E	≤ 0.1 ppm
isophorone diamine	D	> 0.1 to ≤ 1 ppm
Notes:	Occupational exposure banding is a process of assigning chemicals into sadverse health outcomes associated with exposure. The output of this process of exposure concentrations that are expected to protect worker health	ocess is an occupational exposure band (OEB), which corresponds to a

MATERIAL DATA

For benzene-1,3-dimethanamine (m-xylene-alpha,alpha'-diamine; m-xylenediamine; m-xylyldiamine) Saturates in air at 219.5 mg/m3 (39.5 ppm) at 25 deg C.

Exposure controls

Exposure controls	-paduro controlo						
Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard.						

Version No: **2.2** Page **4** of **9** Issue Date: **08/04/2022**

RESENE SQUASH COURT COATING BASE

Print Date: 08/04/2022

Personal protection	
Eye and face protection	► Chemical goggles.
Skin protection	See Hand protection below
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots. NOTE: The material may produce skin sensitisation in predisposed individuals. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer.
Body protection	Overalls
Respiratory protection	Not required for properly ventilated areas. Where the concentration of vapours in the breathing zone approaches or exceeds the "Exposure Standards" respiratory protection is required. Type A Filter of sufficient capacity.

SECTION 9 Physical and chemical properties

Information on basic physical	and chemical properties		
Appearance	White thick solution		
Physical state	Liquid	Relative density (Water = 1)	1.98-2.04
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	9.5-11.5	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	859-1370
Initial boiling point and boiling range (°C)	100	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available BuAC = 1	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	48
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (Not Available%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	9

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	▶ stable.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Version No: **2.2** Page **5** of **9** Issue Date: **08/04/2022**

RESENE SQUASH COURT COATING BASE

Print Date: 08/04/2022

Inhaled	Evidence shows, or practical experience predicts, that the n individuals, following inhalation.	naterial produ	ces irritation of the respiratory systen	n, in a substantial number of			
Ingestion	The material can produce chemical burns within the oral car	The material can produce chemical burns within the oral cavity and gastrointestinal tract following ingestion.					
Skin Contact	The material can produce chemical burns following direct contact with the skin. Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects.						
Eye	The material can produce chemical burns to the eye following	ng direct cont	act.				
Chronic	Long-term exposure to respiratory irritants may result in dist Practical experience shows that skin contact with the mater individuals, and/or of producing a positive response in expe Limited evidence suggests that repeated or long-term occup biochemical systems.	ial is capable rimental anim	either of inducing a sensitisation read als.	ction in a substantial number of			
DESCRIP SOULAND SOURT	TOXICITY		IRRITATION				
RESENE SQUASH COURT COATING BASE	Not Available		Not Available				
	Tito / I valuable		The triangle				
	TOXICITY	IRRITATIO	M				
	dermal (rat) LD50: >2000 mg/kg ^[1]		verse effect observed (not irritating) ^{[1}	1]			
alcohols C11-15 secondary ethoxylated	Oral (Rat) LD50; >=2000 mg/kg ^[1]	· ·	t): 500 mg(open) mild				
·	Oral (Nat) LD30, >=2000 Highg: 2	· ·	dverse effect observed (not irritating)[1]			
		Olani. No de	verse enect observed (not initiating)				
	TOXICITY		IRRITATION				
	Dermal (rabbit) LD50: 2000 mg/kg ^[2]		Eye (rabbit): 0.05 mg/24h SEVERE				
m-xylenediamine	Inhalation(Rat) LC50; 0.8 mg/l4h ^[1]		Skin (rabbit): 0.75 mg/24h SEVERE				
	Oral (Rat) LD50; >200 mg/kg ^[1]						
	Stat (Nat) 2200, 7200 mg/kg						
	TOXICITY			IRRITATION			
	dermal (rat) LD50: >2000 mg/kg ^[1]		Not Available				
isophorone diamine	Inhalation(Rat) LC50; >=1.07<=5.01 mg/l4h ^[1]			Technologic			
	Oral (Rat) LD50; 1030 mg/kg[²]						
Legend:	Nalue obtained from Europe ECHA Registered Substanc specified data extracted from RTECS - Register of Toxic Eff			cturer's SDS. Unless otherwise			
ALCOHOLS C11-15 SECONDARY ETHOXYLATED	Polyethers, for example, ethoxylated surfactants and polyethylene glycols, are highly susceptible towards air oxidation as the ether oxygens will stabilize intermediary radicals involved. Human beings have regular contact with alcohol ethoxylates through a variety of industrial and consumer products such as soaps, detergents, and other cleaning products. Alcohol ethoxylates are according to CESIO (2000) classified as Irritant or Harmful depending on the number of EO-units: EO < 5 gives Irritant (Xi) with R38 (Irritating to skin) and R41 (Risk of serious damage to eyes) EO > 5-15 gives Harmful (Xn) with R22 (Harmful if swallowed) - R38/41 EO > 15-20 gives Harmful (Xn) with R22-41 >20 EO is not classified (CESIO 2000) Oxo-AE, C13 EO10 and C13 EO15, are Irritating (Xi) with R36/38 (Irritating to eyes and skin). AE are not included in Annex 1 of the list of dangerous substances of the Council Directive 67/548/EEC						
	In general, alcohol ethoxylates (AE) are readily absorbed through the skin of guinea pigs and rats and through the gastrointestinal mucosa of rats. For high boiling ethylene glycol ethers (typically triethylene- and tetraethylene glycol ethers): Skin absorption: Available skin absorption data for triethylene glycol ether (TGBE), triethylene glycol methyl ether (TGME), and triethylene glycol ethylene ether (TGEE) suggest that the rate of absorption in skin of these three glycol ethers is 22 to 34 micrograms/cm2/hr, with the methyl ether having the highest permeation constant and the butyl ether having the lowest.						
M-XYLENEDIAMINE	Allergic reactions which develop in the respiratory passages allergen with specific antibodies of the IgE class and belong Particular attention is drawn to so-called atopic diathesis whathma and atopic eczema (neurodermatitis) which is assoc Exogenous allergic alveolitis is induced essentially by allerg lymphocytes) may be involved. For benzene-1,3-dimethanamine (m-xylene-alpha,alpha'-di The toxicity via oral administration and inhalation was tissue contact sites. The material may produce severe skin irritation after prolong.	in their react nich is charac ciated with indien specific in amine) e damage in t	tion rates to the manifestation of the iterised by an increased susceptibility treased IgE synthesis. Innune-complexes of the IgG type; ce the digestive and respiratory organs, it d inflammation.	mmediate type. to allergic rhinitis, allergic bronchial ell-mediated reactions (T respectively, which are the first			
	The material may produce severe skin irritation after prolonged or repeated exposure, and may produce a contact dermatitis (nonallergic). While it is difficult to generalise about the full range of potential health effects posed by exposure to the many different amine compounds, characterised by those used in the manufacture of polyurethane and polyisocyanurate foams, it is agreed that overexposure to the majority of						

Version No: **2.2** Page **6** of **9** Issue Date: **08/04/2022**

RESENE SQUASH COURT COATING BASE

Print Date: 08/04/2022

these materials may cause adverse health effects. Many amine-based compounds can induce histamine liberation, which, in turn, can trigger allergic and other physiological effects, including bronchoconstriction or bronchial asthma and rhinitis. F Systemic symptoms include headache, nausea, faintness, anxiety, a decrease in blood pressure, tachycardia (rapid heartbeat), itching, erythema (reddening of the skin), urticaria (hives), and facial edema (swelling). For isophorone diamine Based on a limited skin irritation study with rabbits and rats, isophorone diamine is deemed to be a strong irritant (duration of the exposure not reported) and corrosive after repeated application. ISOPHORONE DIAMINE The material may be irritating to the eye, with prolonged contact causing inflammation. The material may produce respiratory tract irritation. The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). **RESENE SQUASH COURT COATING BASE &** Asthma-like symptoms may continue for months or even years after exposure to the material ends. M-XYLENEDIAMINE & The following information refers to contact allergens as a group and may not be specific to this product. ISOPHORONE DIAMINE

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	~	Reproductivity	×
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	×
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend:

🗶 – Data either not available or does not fill the criteria for classification

🧪 – Data available to make classification

SECTION 12 Ecological information

Toxicity

RESENE SQUASH COURT	Endpoint	Te	est Duration (hr)		Species Va		Value	Value		Source	
COATING BASE	Not Available	N	ot Available Not Availab		able Not Available		able	Not Available			
alcohols C11-15 secondary	Endpoint		Test Duration (hr)			Species		Value		Source	
ethoxylated	NOEC(ECx)		672h			Crustacea		0.08mg/	1	2	
m-xylenediamine	Endpoint	Test	Duration (hr)	s	pecies				Value	Source	
	BCF	1008	1008h		ish				<0.3	7	
	NOEC(ECx)	504h		C	Crustacea				4.7mg/l	2	
	LC50	96h		F	Fish			75mg/l		2	
	EC50	72h		А	Algae or other aquatic plants				12mg/l	2	
	EC50	48h	48h Crustacea					15.2mg/l	2		
	Endpoint	Test [Ouration (hr)	Spe	cies			Valu	e	Source	
	BCF	1008h	1	Fish		ish		<0.3		7	
	LC50	96h	96h		Fish			70mg/l		1	
isophorone diamine	EC50	72h	?h		Algae or other aquatic plants			37mg/l		1	
	EC50	48h	48h		Crustacea			14.6-21.5mg/l		4	
	NOEC(ECx)	72h		Algae or other aquatic plants			1.5mg/l		1		
Legend:			icity Data 2. Europe E xicity Data 5. ECETO								

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
m-xylenediamine	HIGH	HIGH
isophorone diamine	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
m-xylenediamine	LOW (BCF = 2.7)
isophorone diamine	LOW (BCF = 3.4)

Mobility in soil

Ingredient	Mobility	

Version No: **2.2** Page **7** of **9** Issue Date: **08/04/2022**

RESENE SQUASH COURT COATING BASE

Print Date: 08/04/2022

Ingredient	Mobility
m-xylenediamine	LOW (KOC = 914.6)
isophorone diamine	LOW (KOC = 340.4)

SECTION 13 Disposal considerations

Waste treatment methods

- DO NOT allow wash water from cleaning or process equipment to enter drains.
- Recycle wherever possible.

Product / Packaging disposal

Consult manufacturer for recycling option.

Resene Paintwise accepts residual unwanted paint and packaging. See Resene website for Paintwise information. Or contact a Local Authority for the disposal information. Do not discharge the substance into the environment.

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package.

Do not allow product or wash water from cleaning or process equipment to enter drains or watercourses. It may be necessary to collect all wash water for treatment before disposal. The generation of waste should be avoided or minimised wherever possible.

Disposal of this product should comply with Hazard Substances (Disposal) Notice 2017 (EPA Consolidation 30 April 2021).

For treating and discharging processes contact your local authority.

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
alcohols C11-15 secondary ethoxylated	Not Available
m-xylenediamine	Not Available
isophorone diamine	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
alcohols C11-15 secondary ethoxylated	Not Available
m-xylenediamine	Not Available
isophorone diamine	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002670	Surface Coatings and Colourants Subsidiary Hazard Group Standard 2020

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

alcohols C11-15 secondary ethoxylated is found on the following regulatory lists

New Zealand Approved Hazardous Substances with controls
New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification
of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

m-xylenediamine is found on the following regulatory lists

New Zealand Inventory of Chemicals (NZIoC)

isophorone diamine is found on the following regulatory lists

New Zealand Workplace Exposure Standards (WES)

Version No: 2.2 Page 8 of 9 Issue Date: 08/04/2022

RESENE SQUASH COURT COATING BASE

Print Date: 08/04/2022

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantities
Not Applicable	Not Applicable

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
6.5A or 6.5B	120	1	3	

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
New Zealand - NZIoC	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	08/04/2022
Initial Date	26/07/2017

SDS Version Summary

Version	Date of Update	Sections Updated
1.2	08/04/2022	Classification, Environmental, Exposure Standard

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory

NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

Version No: 2.2 Page 9 of 9 Issue Date: 08/04/2022

RESENE SQUASH COURT COATING BASE

Print Date: 08/04/2022

TSCA: Toxic Substances Control Act

TCSI: Taiwan Chemical Substance Inventory
INSQ: Inventario Nacional de Sustancias Químicas
NCI: National Chemical Inventory
FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.