

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase. Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

# Ceiling Paint

## waterborne flat

### interior

KEEP OUT OF REACH OF CHILDREN

LL3140210F 11/21

### SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. This material is quite bland; with vapour, occasional skin contact and even minor ingestion having negligible hazard. Repeated skin contact may, and any eye contact will, cause irritation.

### PRECAUTIONS

USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Avoid release to the environment.

### FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF ON SKIN (or hair): Rinse skin with plenty of soap and water. If skin irritation or rash occurs get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists, get medical advice or attention.

When seeking medical advice take this container with you. Further information can be obtained from  
AUST. POISONS INFORMATION CENTRE 131 126  
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)  
or call Resene 0800 737 363.

For use as a decorative/protective coating.

**SPILLS:** Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

**CLEANING PAINT EQUIPMENT:** Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Crown Ceiling Paint is a waterborne flat finish recommended for use on ceilings of living rooms, bedrooms and dining rooms where a flat finish is required. Easy to apply with low spatter. One coat is often enough to achieve complete hiding.

### Preparation

- Ensure surfaces are in sound condition, thoroughly sanded, dry and free from dirt, dust and loose material.

- If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80). Oil, grease, fly spots and nicotine stains should be removed using either Resene Emulsifiable Solvent Cleaner (see Data Sheet D804) or sugar soap. Rinse clean with water.

- Where staining is present the source must be removed.

- Fill cracks and holes in ceiling before sealing.

- **All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**

- Consult your Resene ColorShop or reseller for technical advice on painting in wet areas, such as bathrooms.

- This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

### Priming

- Paperfaced plasterboard, fibrous plaster and their stoppings should be primed (e.g. Crown Wallboard Sealer).

- Hardboard must be sealed (e.g. Resene Sureseal – see Data Sheet D42) to promote flow of the topcoats. Use Resene Sureseal if the surface is water stained.

- Some 'soft' paperfaced plasterboard preparatory products and undercured gypsum based stoppings may not be suitable basecoats for painting under stressed conditions. Reinforcement with a saturation coat of a fully penetrating primer (such as Resene Sureseal) may be required. Use Resene Sureseal if the surface is water stained.

- All surfaces that are highly absorbent, in poor condition, friable, powdery or stained must be primed with Resene Sureseal.

- Heavily stained surfaces may require a second coat of Resene Sureseal.

### Application

- Apply one or two coats, allowing at least two hours between coats.

- Maintain good ventilation throughout the drying and curing period to ensure the paint is properly cured. Poor ventilation may inhibit curing and performance.

### Maintenance

(after a minimum of four weeks' drying)  
See the Resene Caring for your paint finish brochure or the Resene website for full cleaning instructions.

### Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

## Quick check

**Use on:** Interior ceilings.

**Gloss level:** Flat.

**Coverage:** 10 square metres per litre.

The spreading rate recommended for this product will achieve hiding in one coat for most colours. Increased spreading rates can be used but additional coats may be needed to achieve hiding. See the Resene website for more information.

**Dry time (minimum):** 45 minutes. Do not apply at temperatures below 10°C or when temperatures are liable to drop below this during the drying period. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

**Recoat time (minimum):** 2 hours.

**Primer required:** Dependent on surface.

**Usual number of coats:** 1-2.

**Application method:** Brush, speed brush, roller or spray.

**Thinning and clean up:** Water. May be thinned with up to 5% clean tap water.

**Hot conditions:** In hot conditions may be thinned with up to 5% Resene Hot Weather Additive to slow drying.

**Colour:** White or colours off white.

**Before use:** Stir well with a wide flat stirrer.

In every case it is recommended that the appropriate Safety Data Sheet is consulted prior to application.

  
**Crown**  
PAINTS

In Australia: Resene Paints (Aust) Limited  
7 Production Ave, PO Box 918, Ashmore City, QLD 4214  
Ph 1800 738 383 Visit [resene.com.au](http://resene.com.au)

In New Zealand: Resene Paints Limited  
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045  
Ph (04) 577 0500 Visit [resene.co.nz](http://resene.co.nz)

Manufactured under a quality system certified as complying with ISO 9001 by Telarc SAI, an accredited certification body. Printed on paper produced in manufacturing facilities which comply with environmental management systems EMAS and ISO 14001, using vegetable-based inks. Please recycle.