

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase. Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

# Resene

## Aquaclear Natural

### waterborne clear

interior

**WARNING**

KEEP OUT OF REACH OF CHILDREN



**FLAT**

net  
contents  
1 litre

LL2420001F 9/19

net contents 1 litre

LL2420001B 9/19

### SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Causes mild skin irritation. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

### PRECAUTIONS

USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Wear protective gloves and clothing, eye and face protection. Avoid release to the environment.

### FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation occurs get medical advice.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

When seeking medical advice take this container with you.

Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D59.

**SPILLS:** Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

**CLEANING PAINT EQUIPMENT:** Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

### Quick check

**Use on:** Interior timber walls and ceilings.

**Gloss level:** Flat natural. Resene Aquaclear Satin, Semi-Gloss and Gloss are also available for interior timber surfaces.

**Coverage (average):** 10-12 square metres per litre per coat. Spreading rates are given for bare timber - take care not to overspread on sealed surfaces.

**Dry time (minimum):** 30 minutes. Do not apply at temperatures below 10°C or when temperatures are liable to drop below this during the drying period. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

**Recoat time (minimum):** 2 hours.

**Primer required:** No.

**Usual number of coats:** Three - minimum. An additional coat is recommended in areas prone to higher wear and tear.

**Application method:** Apply by roller using a Resene No.4 roller sleeve, spray, speed brush or a synthetic bristle brush.

**Thinning and clean up:** Water. First coat may be thinned with up to 10% clean water.

**In hot and dry conditions:** Application is difficult at high temperatures and low humidity. Up to 5% Resene Hot Weather Additive may be added.

**Colour range:** Milky - dries clear.

**Before use:** Stir well with a wide flat stirrer.



Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Open for more instructions.

Resene Aquaclear Natural is a waterborne clear flat finish for interior timber walls and ceilings, designed to enhance and protect timber from everyday wear and tear. May also be used with Resene Colorwood Enhance to add extra depth and colour to timber.

### Preparation

- Ensure surfaces to be coated are in sound condition, dry, free from dirt, dust, loose material, oil and grease.
- If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80).
- Stop all nail holes and cracked timber with a suitable filler.
- Thoroughly sand surfaces prior to coating. Finish off with fine sandpaper, remembering always to sand with the grain.
- Previously varnished surfaces must be sanded to remove all gloss and provide a key for good adhesion. If old varnish is flaking everything must be removed to ensure a uniform appearance.

**• All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old asbestos containing building materials may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**

- This product may be used to coat a wide variety of surfaces. If the surface you propose to coat is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

### Application

- For uncoated surfaces thin first coat up to 10% with clean water.
- Stir thoroughly with a wide flat stirrer before and during use.
- Apply with a speed brush, synthetic bristle brush or Resene No.4 roller (product can be sprayed). Apply evenly. Avoid working over a surface that has begun to set as this

will give a patchy appearance.

- Allow at least two hours between coats.
- To avoid foaming of material, do not brush or roll excessively.
- Do not apply in direct sunlight.
- Requires 72 hours for coating to reach full cure.
- Maintain good ventilation throughout the drying and post application curing period to ensure the paint is properly cured. This may require use of an extraction system when painting in marginal painting conditions. Do not use gas or diesel burners to heat coated area as these produce water that will inhibit drying and curing. Poor ventilation may affect appearance and performance.

### Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information.

Please ensure that use of this product is compatible with the substrate and surface preparation method. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.



Aquaclear SDS



Aquaclear TDS

# Resene

the paint the professionals use

**In Australia:** Resene Paints (Aust) Limited  
7 Production Ave, PO Box 924, Beenleigh, Qld 4207  
Ph 1800 738 383 Visit [www.resene.com.au](http://www.resene.com.au)

**In New Zealand:** Resene Paints Limited  
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045  
Ph (04) 577 0500 Visit [www.resene.co.nz](http://www.resene.co.nz)

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAI, an accredited certification body. Printed on environmentally responsible paper, which meets with the requirements of environmental management system EMAS. Printed using de-inkable toners for recycling with no solvent emissions.