

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase. Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

LL1920280 6/23

WHITE



9

Resene

Colour Enhance

80 mL

(enough to colour 2 litres)


Rejuvenate and enhance colour with Resene Colour Enhance. For extra colour on timber mix Resene Colour Enhance with Resene Aquaclear or Resene Qristal ClearFloor 1K, or for concrete mix with Resene Concrete Clear or Resene Concrete Wax.

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 918, Ashmore City, QLD 4214
Ph 1800 738 383 Visit resene.com.au

In New Zealand: Resene Paints Limited
Vogel St, Lower Hutt, PO Box 38242, Wgtn Mail Centre
Ph (04) 577 0500 Visit resene.co.nz

Please recycle.

Open to read more instructions.

- 
- Shake well before addition to the base product.
 - Add 40 mL (half this bottle) per litre. 1 capful - approx. 10 mL. You can add less for a more subtle effect. For a darker effect apply a second coat with Resene Colour Enhance mixed in.
 - Stir the tinted base with a wide flat stirrer to thoroughly incorporate the Resene Colour Enhance.
 - Back add to the original Resene Colour Enhance pack, cap tightly and shake to incorporate any Resene Colour Enhance not transferred in the first transfer. Add to the bulk material and re-stir.
 - Test your mixed product on an inconspicuous area to check you are happy with the colour and finish before coating the full area.

- Apply a full even wet coat of your product that has been mixed with Resene Colour Enhance working in one direction along a section. Avoid overlapping as overlaps will appear more opaque. Addition of Resene Hot Weather Additive at the maximum rate will assist in maintaining a longer open time when you are applying product to large areas, such as flooring.

Do not mix Resene Colour Enhance with Resene Qristal ClearFloor 2K.

Resene

the paint the professionals use

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. This material is quite bland; with vapour, occasional skin contact and even minor ingestion having negligible hazard. Repeated skin contact may, and any eye contact will, cause irritation.

PRECAUTIONS

USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions.

FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF ON SKIN (or hair): Rinse skin with plenty of soap and water. If skin irritation or rash occurs get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Continue rinsing. If eye irritation persists get medical advice or attention.

If medical advice is required have product container or label at hand.