

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.

Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

**WARNING**

KEEP OUT OF REACH OF CHILDREN

# Resene

## Swimming Pool Paint

A-LL49404SP 11/15

**WARNING**

Read label before use. Keep out of reach of children. May be harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction Causes eye irritation. Suspected of causing cancer. Suspected of causing damage to fertility or the unborn child. May cause respiratory irritation. Harmful if inhaled. Vapours may cause dizziness or drowsiness. Toxic to the aquatic environment with long lasting effects.

**PRECAUTIONS**

AVOID BREATHING VAPOUR. USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Do not handle until all safety precautions have been read and understood. Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Store locked up. Ground/bond container and receiving equipment, as product is volatile and may generate a hazardous atmosphere. Use explosion proof electrical/ventilating/lighting and other equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves, eye/face protection. Use other personal protective equipment as required. Do not allow contaminated work clothing out of the workplace. Wash thoroughly after handling. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint. Do not contaminate any water supply. Avoid release to the environment.

**FIRST AID**

IF SWALLOWED: Rinse mouth.  
IF ON SKIN (or hair): Remove contaminated clothing and wash before re-use. Rinse with plenty of soap and water.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical attention/advice.  
IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.  
Call a POISON CENTRE if you feel unwell.  
When seeking medical advice take this container with you.  
Further information can be obtained from  
AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.  
NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.  
CONTAINS: Aromatic Hydrocarbons 570-630 gms/L, chloroparaffin 110-120 gms/L, Epoxy resin 10-15 gms/L.  
For use as a decorative/protective coating.  
For full technical instructions see Data Sheet D69.

**SPILLS:** Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

**CLEANING PAINT EQUIPMENT:** Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with Resene Brush Cleaner or Resene Thinner No.11. Do not allow thinners to enter drains. Refer to your local Council for disposal of dirty thinners.

**IN CASE OF FIRE:** Use foam, CO<sub>2</sub>, dry chemical for extinction.



MAGIC BLUE

Resene Swimming Pool Paint is formulated for direct application to suitably prepared concrete swimming pools or to maintain pools coated in a compatible coating system. A single pack pool paint that has excellent intercoat adhesion for easy maintenance and touch up.

**Surface preparation**

Refer to the Resene Swimming Pool Paint disclaimer, available from your Resene ColorShop or the Resene website, before commencing work.

**New concrete**

- Leave concrete to cure for a minimum of 28 days before painting. Ensure surface is free of laitance, form release agents, curing membranes, oil, grease and other penetrating contaminants.
- If oil or grease are present, degrease with Resene Paint Prep and Housewash (see Data Sheet D812).
- Glossy or smooth concrete must be profiled by light abrasive blasting or grinding. Surface profiling methods should produce a uniform surface texture resembling 180 grit sandpaper. Repeat the blasting if necessary until the required surface texture is achieved.
- Concrete surfaces cured with curing membranes or contaminated with form oils must be completely cleaned by abrasive blasting or grinding (acid etching is not suitable as this procedure will not normally remove these compounds).

**Old unpainted concrete**

- Remove any powdery material by waterblasting.
- Treat with Resene Paint Prep and Housewash to remove oils, dirt and other contaminants. Rinse with clean water.
- Ensure surface is thoroughly dry (see Data Sheet D69 for test method).

**Repaint (Resene Swimming Pool Paint)**

- Treat with Resene Paint Prep and Housewash to remove chalking, oils, dirt and other contaminants. Rinse with clean water.
- Ensure bare concrete is sound and thoroughly dry (see Data Sheet D69 for test method).
- Spot prime bare areas of concrete with Resene Swimming Pool

Paint thinned 10-15% with Resene Thinner No.11.

**Repaint (except Resene Swimming Pool Paint)**

- Totally remove the existing paint system. This can be best achieved by abrasive blasting (wet or dry), high pressure water jetting or grinding. Complete removal means the surface must be free of any visible residues of the old paint. This will often give an aggregate rich surface, which must be re plastered prior to repainting.
- Ensure bare concrete is sound and thoroughly dry (see Data Sheet D69 for test method).
- Prepare areas of glossy or smooth concrete as for new concrete.
- If the surface you propose to paint is unsound or not referred to, contact your local Resene ColorShop for technical assistance.

**Application**

- Roller: Use short pile, solvent resistant roller and apply 2-3 coats. Roller application is always recommended for the first coat onto bare concrete. To avoid air entrapment do not roll excessively.
- Airless spray: Standard industrial equipment with a 30:1 pump ratio and a 17-21 thou fluid tip.
- Conventional spray: JGA502 gun with an E fluid tip and needle, and 704 or 768 air cap or equivalent.
- Brush: Suitable for small areas or touch up.

**Solvents released from the wet paint are heavier than air and will accumulate at the bottom of the pool. Adequate ventilation must be maintained during application and drying for health, safety and performance reasons. Not for use in pools heated above 28°C. Some water treatments are more aggressive to paints than others. Resene Swimming Pool Paint will naturally chalk over time. The rate of chalking will depend upon the degree of cure prior to filling, pool treatment methods and water temperature. Chalking is an irreversible process.**

**Be PaintWise**

For tips on minimising the impact of your decorating on the environment see the Resene website.



UN NO. 1263 – PAINT

FLAMMABLE LIQUID AND VAPOUR

Keep away from ignition sources such as heat/ sparks/ open flame/ hot surfaces. No smoking.



**Resene**  
the paint the professionals use



**In Australia:** Resene Paints (Aust) Limited  
7 Production Ave, PO Box 924, Beenleigh, Qld 4207  
Phone 1800 738 383 Fax 1800 064 960  
Email advice@resene.com.au or visit www.resene.com.au

**In New Zealand:** Resene Paints Limited  
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045  
Phone (04) 577 0500 Fax (04) 577 0600  
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SA, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

net contents 4 litres

tinter included

Quick check

**Use on:** Suitably prepared concrete swimming pools.

**Coverage:** Approximately 9 square metres per litre per coat.

**Dry time (minimum):** Touch dry: 2 hours. To immersion: 7 days (minimum) (preferably 14 days).

**Recoat time (minimum):** 12 hours. Maximum: Indefinite when overcoating with Resene Swimming Pool Paint.

**Usual number of coats:** Two - maintenance. Three - bare concrete.

**Thinning and clean up:** Resene Thinner No.6 (spray). Resene Thinner No.11 (brush/roller).

**Colour:** Magic Blue.

**Before use:** Stir well with a wide flat stirrer.

COATED POOL MUST BE LEFT TO CURE FOR AT LEAST 1-2 WEEKS BEFORE FILLING. THE COATING MUST LOSE ALL SOLVENT BEFORE IT WILL FULLY CURE. SOLVENT DISPLACEMENT CAN BE INCREASED BY PLACING A LARGE FAN IN THE BOTTOM OF THE POOL 48 HOURS AFTER APPLICATION OF THE FINAL COAT, RUN FAN OVER THE COURSE OF WEEK TO ENSURE SOLVENT IS DISPLACED FROM POOL. IF POOL HAS A SLOPE PLACE FAN AT THE DEEPEST POINT IN THE POOL AS THIS IS THE AREA WHERE THE MOST SOLVENT WILL ACCUMULATE.

Enjoy the Resene Promise of Quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.