

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.

Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

KEEP OUT OF REACH OF CHILDREN

# Resene

## Water Lockout

### watertight membrane

#### exterior use only

A-LL3801004 6/19

#### SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. This material is quite bland; with vapour, occasional skin contact and even minor ingestion having negligible hazard. Repeated skin contact may, and any eye contact will, cause irritation.

#### PRECAUTIONS

USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Avoid release to the environment.

#### FIRST AID

IF SWALLOWED: Rinse mouth. Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation occurs get medical advice.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

For full technical instructions see Data Sheet D75.

**SPILLS:** Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

**CLEANING PAINT EQUIPMENT:** Brush/roll out as much paint as possible on to newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.



BLACK

**Resene Water Lockout is a versatile high build liquid watertight membrane based on a urethane modified bitumen emulsion. Cures to a seamless highly elastic and durable film that adheres well to most substrates to block water ingress.**

#### Preparation

- Ensure all surfaces to be treated are dry, free from dust, dirt and loose materials, oil and grease.
- Remove oil and grease from surface using Resene Paint Prep and Housewash (see Data Sheet D812).
- Pre-dampen hot, dry or very absorbent surfaces, such as concrete, with water prior to applying Resene Water Lockout.
- This product may be used to treat a wide variety of surfaces. If the surface you propose to treat is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or Reseller.

#### Application

- Apply each coat at right angles to the dry preceding coat.
- For flat surfaces, a pour and spread application technique using a squeegee may be used to achieve a uniform wet film thickness and to fill voids on horizontal surfaces.
- May be sprayed but requires specialist spray equipment. Consult Resene Technical Services for advice when considering spray application.
- On all weak points such as cracks, around pipe penetrations or at the wall/floor junction use a woven fibreglass cloth between the first two coats of Resene Water Lockout. Roll the fibreglass cloth into the first coat while wet and leave to fully

dry before application of the second coat of Resene Water Lockout.

- Maintain good ventilation throughout the drying and curing period to ensure the treatment is properly cured. Poor ventilation may inhibit curing and performance.
- Do not use as a curing membrane on surfaces to be painted.

#### Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information.



Water Lockout SDS

# Resene

the paint the professionals use



Water Lockout TDS

In Australia: Resene Paints (Aust) Limited  
7 Production Ave, PO Box 924, Beenleigh, Qld 4207  
Ph 1800 738 383 Visit [www.resene.com.au](http://www.resene.com.au)

In New Zealand: Resene Paints Limited  
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045  
Ph (04) 577 0500 Visit [www.resene.co.nz](http://www.resene.co.nz)

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAL, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

net contents 4 litres

#### Quick check

**Use on:** Masonry walls, in situ concrete – walls/floors, plastered/rendered walls, retaining walls and wood planter box interiors.

**Gloss level:** Satin.

**Application rate:** Two coats at one square metre per litre per coat. Additional coats may be required to achieve this spreading rate, especially on vertical surfaces.

**Dry time (minimum):** 1-3 hours. Full dry 3-4 days.

Do not apply at temperatures below 10°C or when temperatures are liable to drop below this during the drying period. Drying is slowed by thicker coats, low temperatures and high humidity. The barrier properties of the surface skin can mean that very thick applications can take a very long time to through dry.

**Primer required:** Typically not required.

**Application method:** Brush, roller (high solids sleeve) or squeegee (flat surfaces only).

**Thinning:** Do not thin.

**Clean up:** Clean with water while wet. Once dry, use Resene Thinner No.2.

**Colour:** Brown when wet, black when dry. Recommended for non aesthetic areas of buildings.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy. In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method. Resene does not accept any responsibility for the application of incorrect product to substrate. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.