

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.
Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

net contents 1 litre

A-LL370101 8/19

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Causes serious eye irritation. May cause damage to organs through prolonged or repeated exposure. Causes skin irritation. May be harmful if swallowed and enters airways. Harmful to aquatic life with long lasting effects.

PRECAUTIONS

DO NOT BREATHE DUST, FUMES, GAS, MIST, VAPOURS OR SPRAYS. Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Store locked up. Wear protective gloves and clothing, eye and face protection. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and intrinsically safe equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid release to the environment.

FIRST AID

IF SWALLOWED: Immediately call a POISON CENTRE, doctor or first aider. Do NOT induce vomiting.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

If exposed or concerned, seek medical advice.

When seeking medical advice take this container with you.

Further information can be obtained from
AUST: POISONS INFORMATION CENTRE 131 126
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)
or call Resene 0800 737 363.

CONTAINS: Naphtha Petroleum, heavy, hydrotreated 260-540 gms/L. For use as a surface preparation coating.

For full technical instructions see Data Sheet D40 (white); D46 (aluminium).

SPILLS: Use appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with Resene Brush Cleaner or mineral turps. Do not allow mineral turps to enter any drains. Refer to your local Council for disposal of dirty mineral turps.

FIRE: Use foam, carbon dioxide or dry chemical powder.

WARNING

KEEP OUT OF REACH OF CHILDREN

Resene

Wood Primer
general purpose
solventborne exterior/interior



WHITE

Resene Wood Primer is based on an oil-modified alkyd resin blended with pigments to give ease of application and good penetration to substrates. Easy to apply, it is flexible and produces the ideal surface for subsequent paint finishes. Resene Wood Primer pigmented (not aluminium variant) is made using a lower odour formulation without the unwanted and strong solvent odours associated with traditional solventborne alkyd resin primers.

Preparation

• Ensure substrates to be coated are in sound condition, dry free from dirt, dust, loose material, oil (including mineral oil based wood finishes or similar) and salt.

• If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80).

• Fill cracks and holes with an appropriate filler after priming.

• Round all sharp timber edges. Any bare timber surface that has been left exposed to the weather for more than one week must be thoroughly sanded or treated with Resene TimberLock (see Data Sheet D48).

• **All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**

• Resene Quick Dry (see Data Sheet D45) must be used as the first coat on Matai, Spotted Gum and Totara.

• Resene Aluminium Wood Primer may be used to block resin bleed from resinous timber areas and knots, to block tannin staining and where a high standard of surface preparation cannot be achieved.

• This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, contact your local Resene ColorShop or reseller.

Application

• Pretreatment with Resene TimberLock is recommended on Cedar and weathered timber surfaces.

• Apply one full coat. Allow 24 hours to dry before topcoating. Resene Wood Primer is best applied by brush to ensure full surface wetting is achieved.

• Where possible prime all timber faces with particular attention to end grains, nailheads, splits, corners and joints.

Overcoating

• Resene Wood Primer requires a minimum of two full topcoats to be applied.

• Resene Wood Primer should not be exposed to the weather for long periods. Consult your Resene ColorShop if recoating after one month.

• For best results Resene Enamel Undercoat (see Data Sheet D44) should be applied over Resene Aluminium Wood Primer.

• Under certain conditions waterborne paints may crawl or ciss over Resene Wood Primer. Wiping with clean turps or a dilute detergent solution will rectify the condition.

Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information.



UN NO. 1263 – PAINT RELATED MATERIAL



Resene
the paint the professionals use



In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Ph 1800 738 383 Visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045
Ph (04) 577 0500 Visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAI, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

Quick check

Use on: Exterior and interior woodwork (except Matai, Spotted Gum and Totara).

Gloss level: Low sheen.

Coverage: 12 square metres per litre per coat.

Dry time (minimum): 6 hours (white) and 24 hours (aluminium).

Recoat time (minimum): 24 hours. Overcoat when hard dry. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

Usual number of coats: One.

Application method: Brush or roller.

Thinning and clean up: Resene Thinner No.2 (lower odour) or mineral turps.

Colour range: White or aluminium.

Before use: Stir well with a wide flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

FLAMMABLE LIQUID AND VAPOUR

Keep away from heat, hot surfaces, sparks, open flames and other sources of ignition.
No smoking.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. When using multiple packs of this product on the same project please mix them together before use. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.